



# Leyard Europe DirectLight Pro Series

LED Video Wall Displays Made in Europe

- Customizable with 0.9, 1.2, 1.5, & 1.8mm pixel pitches
- Full front installation and serviceability
- 1000 nit Brightness fits more environments and content
- Multiple cabinet sizes enable faster install
- Increased bandwidth facilitates fewer components with increased features
- Enables unique installs with tilting and up to 90° corners
- Multiple controller options including ColorLight; Planar WallDirector, and Brompton
- Advanced controls and alarm functions
- Made in Europe



Leyard Europe DirectLight<sup>®</sup> Pro Series fine pixel pitch LED video walls deliver beautiful imagery to suit every indoor, fixed installation application. The front-service video walls feature models with high bandwidth, reducing deployment complexity and maximizing overall efficiency. For wider processing and feature flexibility the displays are compatible with the Planar<sup>®</sup> WallDirector<sup>™</sup> Video Controller, Brompton Technology<sup>®</sup> and Colorlight.



#### DirectLight Pro Complete LED Video Wall Packages

The Leyard Europe DirectLight Pro Complete<sup>™</sup> Video Wall solution is available in convenient sizes and resolutions to reduce the time, complexity and cost of designing and installing a customized LED video wall. We've packaged everything an organization needs in one complete solution. Simply select the video wall size and resolution that best suits the environment and application, and receive the complete package, including the LED display cabinets, video controller, wall mounts, trims, cables and spare modules.

- Complete Direct View LED Video Wall ready to install
- 4K, Full HD, Dual-Full HD video walls in convenient diagonal sizes: 109", 137", 164", 198" and 219"
- Slim profile with full front installation and serviceability
- Leyard Europe Evercare Limited Lifetime Warranty








## Ingrained Efficiency

Video walls are comprised of both 27" and double-tall 36" LED cabinets. Fewer cabinets speed installation and maintenance, and lessens potential for visible seams.



## High Bandwidth at "5G architecture"

Most models offer 5x the bandwidth of competitive solutions, reducing total cost of ownership with fewer cabinets, cables and internal components like receivers and power supplies.




## Powerful Video Controller & Software

The compact Colorlight Controller drives the video wall at native resolution while its corresponding software simplifies setup and management. It captures multiple 4K inputs and supports HDR, ultra-low latency and genlock. Both 5G and fiber outputs are supported.



# Controller Compatibility

Optionally, the new DirectLight Pro Series LED displays can also be equipped with the Planar® WallDirector™ Video Controller or the market-leading Brompton Technology LED video processors instead of the standard controller.



## Turn the Corner

Display modules and cabinets have 45° beveled edges enabling video walls to wrap around 90° corners for unique installations, and opening the displays for use in more creative applications.



# HDR Ready

Displays are ready for High Dynamic Range content, maximizing the image quality of each pixel for brighter whites, darker blacks and more true-to-life colors.



Full HD

Mode DLP0.9 DLP1.2 DLP1.5 DLP1.8

Video

## Configure a Video Wall

Leyard Europe DirectLight Pro Series video walls feature a modular design with display cabinets that stack like building blocks in any configuration. Create video walls with custom sizes, shapes, corners, curves and resolutions.

shap	oes, corne	rs, curves	and resolu	utions.		No.		NY A				
192	0 x 1080	<b>4K</b> <sup>3</sup>	840 x 2160	<mark>8K</mark> 70	680 x 4320	3						
els	1 x 1	2 x 2	3 x 3	4 x 4	5 x 5	6 x 6	7 x 7	8 x 8	9 x 9	10 x 10	11 x 11	12 x 12
	640 x 360	1280 x 720	1920 x 1080	2560 X 1440	3200 x 1800	3840 x 2160	4480 x 2520	5120 x 2880	5760 x 3240	6400 x 3600	7040 x 3960	7680 x 4320
	480 x 270	960 x 540	1440 x 810	1920 x 1080	2400 x 1350	2880 x 1620	3360 x 1890	3840 x 2160	4320 x 2430	4800 x 2700	5280 x 2970	5760 x 3240
	384 x 216	768 x 432	1152 x 648	1536 x 864	1920 x 1080	2304 x 1296	2688 x 1512	3072 x 1728	3456 x 1944	3840 x 2160	4224 x 2376	4608 x 2592
	320 x 180	640 x 360	960 x 540	1280 x 720	1600 x 900	1920 x 1080	2240 x 1260	2560 x 1440	2880 x 1620	3200 x 1800	3520 x 1980	3840 x 2160
o Wall	Wall Sizes											

Area	0.21sqm	0.82sqm	1.85sqm	3.29sqm	5.14sqm	7.41sqm	10.08sqm	13.17sqm	16.67sqm	20.58sqm	24.90sqm	29.63sqm
Diagonal	27″	55″	82″	109″	137″	164″	191″	219″	246″	273″	301″	328″
Meters/Feet	0.3 x 0.6m 1.1 x 2.0ft	0.7 x 1.2m 2.2 x 4.0ft	1.0 x 1.8m 3.4 x 6.0ft	1.4 x 2.4m 4.5 x 7.9ft	1.7 x 3.0m 5.6 x 9.9ft	2.0 x 3.6m 6.7 x 11.9ft	2.4 x 4.2m 7.8 x 14.0ft	2.7 x 4.8m 8.9 x 15.9ft	10.1 x 17.9ft 3.1 x 5.4m	11.2 x 19.8ft 3.4 x 6.0m	12.2 x 21.8ft 3.7 x 6.7m	13.4 x 23.8ft 4.1 x 7.3m



### **Extended Ruggedness & Optics**

Displays are available with Planar<sup>®</sup> ERO-LED<sup>™</sup> (Extended Ruggedness and Optics<sup>™</sup>) protective coating that adds durability in high-traffic and interactive environments.



GEOLOGY ROCKS

Welcome

ia. Jandabia

# Enable Interactivity

Optimize video walls with a custom 32-point touch system and ERO-LED. The touch solution is not limited to a 16:9 aspect ratio, opening the door to more sizes and shapes.



### Always-On Reliability

DirectLight Pro Series displays are designed for missioncritical environments in extended or continuous operation. Control rooms and other applications that can't afford downtime benefit from exceptional performance 24x7 and an optional redundant PSU option.



### Low-Power Standby Mode

For maximum power savings and safety, we offer switched and metered PDUs as optional accessories. The controlled switch-off of the displays allows power cost and CO<sub>2</sub> savings and highest security for your IT and AV infrastructure.



# Specifications

-									
Cabinet Model	DLP 0.9	DLP 1.2	DLP 1.5	DLP 1.8					
Pixel Pitch	0.945mm	1.89mm							
Display Technology	Direct View LED								
Cabinet Resolution	27" - 640 x 360   36" - 640 x 720	27" - 480 x 270   36" - 480 x 540	27" - 384 x 216   36" - 384 x 432	27" - 320 x 180   36" - 320 x 360					
Pixel Density	1,119,789/m²   10,4032/sq ft	629,882/m <sup>2</sup>   58,518/sq ft	403,124/m <sup>2</sup>   37,451/sq ft	279,947/m <sup>2</sup>   26,008/sq ft					
Brightness Max, Calibration On	1,000 cd/m <sup>2</sup>								
Contrast Ratio	10,000:1								
Brightness Uniformity	≥97%								
Colour Uniformity	≥97%								
LED Refresh Rate	3,840 Hz								
<b>Colour Temperature Range</b> (k)	3,000 - 10,000								
Viewing Angle (50% Brightness)	>170° Horizontal; >140° Vertical								
Video Controller Size <sup>1</sup>	1U rack-mounted controller, 19" rack								
Video Input Resolution, Max. <sup>1</sup>	4096 x 2160 @ 60hz								
Frame Rate <sup>1</sup>	50, 60hz								
Video Inputs <sup>1</sup>	1x HDMI2.0, 1x DP1.2, 1x 12G-SDI (w/ HDCP 2.2)								
HDR Support	Yes								
Control	LAN / USB / RS232 control								
Installation & Service Access	Front, tool supplied, module locking feature								
Runtime Duty Cycle (Hours/Day)	24 x 7								
LED Lifetime, Typical	100,000 hrs								
Line Voltage	100-240V AC, 50/60hz								
Power Consumption, Maximum	27" - 135 W   36" - 270 W (656 W/m²)	27" - 135 W   36" - 270 W (656 W/m²)	27" - 135 W   36" - 270 W (656 W/m²)	27" - 135 W   36" - 270 W (656 W/m²)					
Power Consumption, 50% brightness intensity	27" - 87 W   36" - 172 W 27" - 85 W   36" - 170 W 27" - 80 W   36" - 160 W			27" - 75 "   36" - 150 W					
Cabinet Size (W x H x D)	27" - 604.8 × 340.2 × 64.5mm   36" - 604.8 × 680.4 × 64.5mm								
Weight (Cabinet)	27" - 6.94kg (15.3lbs)   36" - 13.2kg (29.1lbs)								
Installation & Service Access	Front Access, module removal. All internal electronics accessible								
Supported Installation Types	ported Installation Types Standard Flat Wall   Forward Tilt: up to 10°   90° exterior corners   Concave faceted curve								
Controller Compatibility	Standard: Colorlight   Optional: Brompton & Planar WallDirector Video Controller								
Redundant PSU Option	Yes								
Storage Temperature/Humidity	-40° to 60° C (-40° to 140° F) / 10-85% relative humidity, non-condensing								
Operating Temperature/Humidity	-20° to 40° C (-4° to 104° F) / 10-80% relative humidity, non-condensing								
Regulatory Compliance	NRTL UL 60950-1 TUV Rheinland, FCC Class A, CE EN60950-1, EN 55032 Class A and EN55024, WEEE, CISPR 32/2015								
Warranty	Leyard Europe EverCare Lifetime Limited Warranty (LE Sales Territories)								
<sup>1)</sup> with standard controller may vary with	h other controller options)								

<sup>1)</sup> with standard controller, may vary with other controller options)

Complete Model	HD109	HD137	HD164	DHD198	UHD164	UHD219			
Display Resolution	1920 x 1080			3840 x 1080	3840 x2160				
Display Size (Diagonal)	109in	137in	164in	198in	164in	219in			
Display Size (W x H)	2419 x 1361mm   7.9ft x 4.5ft	3024 x 1701mm   9.9ft x 5.6ft	3629 x 2041mm   11.9ft x 6.7ft	4839 x 1361mm   15.9ft x 4.5ft	3629 x 2041mm   11.9ft x 6.7ft	4839 x 2722mm   15.9ft x 8.9ft			
Pixel Pitch	1.26mm	1.575mm	1.89mm	1.26mm	0.9mm	1.26mm			
Power Consumption, Maximum	2,230 watts	3,445 watts	4,930 watts	4,390 watts	4,930 watts	8,710 watts			
Display Weight	112kg  247lbs	176kg   388lbs	249kg   547lbs	222kg   489lbs	255kg   561lbs	439kg   965lbs			
Warranty	Leyard Europe EverCare Lifetime Limited Warranty (LE Sales Territories)								
Package Includes	Display wall, Video Controller, Signal cables, Power cables, Wall mount, Trim, Remote Control, and Module Spares (may vary by region)								

www.leyardeurope.eu

Leyard Europe +421-907-775-941 sales.emea@leyardgroup.com Leyard and Planar are trademarks of Leyard Optoelectronics Co., Ltd. and Planar Systems, Inc. All other trademarks and service marks are the property of their holders. Copyright © 2023 Leyard Optoelectronics Co., Ltd. and Planar Systems, Inc and eyevis GmbH. All rights reserved. This document may not be copied in any form without permission from Leyard, Planar or eyevis. Information in this document is subject to change without notice. 06/23