



# Planar URP65-T

## 4K LCD Touch Display

The Planar® URP65-T is a 65" 4K (3840 x 2160) LCD touch screen display with enterprise-level features ideal for collaborative and interactive environments. It features protective glass and pin-point accurate projected capacitive touch that supports up to 50 simultaneous touch points. The 24x7 solution lets users view up to four sources simultaneously and enables administrators to receive remote monitoring email alerts if a designated events occur.

The Planar URP65-T is ENERGY STAR® Certified.



SPECIFICATION	DETAIL
<b>Product Name</b>	URP65-T
<b>Planar Part Number</b>	998-2892-00
<b>Protective Glass</b>	3mm with AG+AF coating
<b>Touch Technology</b>	Projected Capacitive: 50 points
<b>OS Compatibility</b>	Windows 10, 11, Mac OSX and Linux
<b>Display Resolution</b>	Ultra HD (3840 x 2160)
<b>Screen Size</b>	65 in. (diagonal)
<b>Aspect Ratio</b>	16:9
<b>Display Technology</b>	Edge-lit LED LCD
<b>Display Active Area</b>	1428.5mm x 803.7mm (56.2" x 31.6")
<b>Viewing Angle (typ)</b>	178°
<b>Backlight</b>	LED
<b>Backlight life (1/2 brightness)</b>	30,000 hrs (min)
<b>Brightness (w/protective glass)</b>	450 nits
<b>Response Time (typ)</b>	8 ms
<b>Frame Rate</b>	60Hz
<b>Contrast Ratio (typ)</b>	1100:1
<b>Pixel Pitch</b>	0.372 mm
<b>Colour Gamut</b>	72% NTSC
<b>Display Colour</b>	>1 billion colors. Full 10 bit data path
<b>External Connections</b>	DisplayPort 1.2 x 2, HDMI 2.0 x 2 (HDCP 2.2), HDMI 1.4 x 2, VGA x 1
<b>Modes</b>	"3840x2160 @ 24/25/30/50/60Hz; 1080p @ 24/25/30/50/60Hz; 1080i @ 50/60 Hz; 480p, 576p, 720p @ 50/60 Hz"
<b>Display Control</b>	IR, RS-232, LAN, HDMI-CEC, Keypad
<b>Cabinet Dimensions (W x H x D)</b>	1482.7mm x 857.5mm x 78.8mm (58.4" x 33.8" x 3.1")
<b>Cabinet Dimensions with Handles (W x H x D)</b>	1482.7mm x 857.5mm x 78.8mm (58.4" x 33.8" x 3.1")
<b>Orientation</b>	Landscape/Portrait
<b>Bezel Width</b>	1.5mm (0.1")
<b>Display Edge to Active Area</b>	27.0mm (1.1") left and right, 27.1mm (1.1") top and bottom
<b>Weight</b>	50.0 kg (110.2 lbs)

SPECIFICATION	DETAIL
<b>Audio Input</b>	PC Line In
<b>Audio Output</b>	PC Line Out, S/PDIF
<b>Speakers</b>	10W x 2 built-in
<b>Enclosure</b>	Metal, Industrial
<b>Mounting</b>	VESA: 400mm x 400mm
<b>Fanless</b>	Yes
<b>Line Voltage</b>	100-240V; 50/60Hz
<b>Power Consumption (typ)</b>	100W (standby: <0.5W)
<b>AC Output Current (max)</b>	3A
<b>Operating Temperature</b>	0° to +40°C (32° to 104°F) up to 3000m
<b>Humidity</b>	20 - 85% RH (non-condensing)
<b>Options / Features</b>	On/Off scheduling, presets, convenient mounting points for third-party accessories
<b>Auto Brightness Control</b>	Ambient light sensor
<b>Multi-Source Views</b>	PIP, Dual, Quad
<b>Approvals</b>	FCC Class A, CE, cTUVus, RoHS
<b>ENERGY STAR Certified</b>	Yes
<b>TAA Compliance</b>	Yes
<b>Security</b>	No WiFi, no Android O/S, signed and encrypted firmware, tamper-resistant stickers, ability to disable communication interfaces, Secure Shell (SSH) protocol
<b>Warranty</b>	3 years Advance Exchange
<b>Recommended Usage</b>	Up to 24x7
<b>In the Box</b>	URP65-T display, power cord, HDMI cable, IR cable, USB A to B cable, remote control, cable clips, passive stylus, Quick Start Guide
<b>UPC</b>	8 10689 00996 2